ES7412 Specifications

OKI

The A4 colour printer that gets the job done quickly, reliably and to an outstandingly high print quality

A powerful network A4 colour printer you can rely on for the fast production of top quality output – from everyday mono documents to high-end marketing collateral at a surprisingly low cost per page.

The ES7412 is ideal for workgroups within an enterprise, working to tight deadlines. It's easy to use and offers exceptional media flexibility, alongside robust security features for more sensitive work.


Key features

- Low running costs
- Fast duplex printing at 34ppm colour/36ppm in mono
- Generous paper capacity up to 1,690 sheets for large workgroups
- Prints on stocks up to 250gsm heavier than any comparable printer
- Security features protect sensitive information and IP
- Store templates and documents on the device for all users to print without authentication (Shared Print)
- Citrix Xen app 7.6 compatibility ideal for virtual network environment



Advanced connectivity

- Wireless Direct feature offers safe simultaneous connection of wired and wireless networking
- Gigabit Ethernet enables fast transfer of large colour files across the network
- Google Cloud Print ready, enabling printing on the move
- Optional Wireless LAN Module available





Simple to set-up, use and own

- Easy to set-up and get started
- When new features are available you can update the device via the OKI portal

Important security features

- Keep documents confidential with Private Print and optional Card Release*, so users can view all print jobs before selecting which ones to print
- Internet Protocol Security (IPSec) compliance, ensuring securing that documents are safely sent and received



Cost and energy saving

- Print marketing materials in-house, thanks to outstanding print quality and media flexibility
- Deep Sleep mode saves energy, Auto-Off mode automatically powers down to less than 0.5W when not in use
- Toner Save to reduce cost, when printing draft or internal documents
- Duplex printing reduces paper usage (optional on ES7412n)
- LED technology means no moving parts for a longer life



ES7412 - Colour and Mono Printer

Printer		GENERAL FEATURES	
A4 Print speed	34ppm colour, 36ppm mono	Memory	Standard RAM: 256MB; Maximum RAM: 768MB
Time to first print	9 seconds colour, 8 seconds mono		Optional SDHC Memory Card4: 16GB
	Up to 60 seconds from power on and up to 35 seconds from power save	Operating conditions	Operating temperature/humidity: 10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended)
INTERFACE AND SOFTWARE			Storage temperature/humidity: -10°C to 43°C, 10% to 90%RH
		Power supply	Single phase 220 to 240VAC, frequency 50/60Hz +/- 2%
Connectivity	USB 2.0 Device, 10Base-T/100Base-TX/1000Base-T Ethernet, Wireless IEEE802.11a/b/g/n (Optional)	Power consumption	Typical: 600W; Max: 1300W; Idle: 100W (average); Power save: <15W; Deep Sleep: <1.2W; Auto-Off: <0.5W
Printer languages	PCL6 (XL3.0), PCL5c, PostScript 3 (emulation), PDF v1.7, SIDM (IBM-PPR, EPSON-FX), XPS	Noise level	Operating: 54dB(A); Standby: 37dB(A); Power save: Background level
Network & protocols	POP3, SNMPv1&v3, SNTP, IPP, IPPS, WSD Print, LLTD, IEEE802.1X, LPR, Port9100, Telnet, FTP, Google Cloud Print, Wireless IEEE802.11a/b/g/n, WEP, WPA, WPA2, Personal, Enterprise Windows Vista (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit) / Windows 7 (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Windows	Dimensions (WxDxH)	435 x 604 x 389mm
		Weight⁵	32kg
			Maximum: 100,000 pages/month;
		Duty cycle	Recommended: 6,000 pages/month
		Warranty	3 years extended warranty upon registration within 30 days of purchase^
OS Compatibility ¹		Product order number	ES7412n: 46406106 ES7412dn: 46406106DN
	Linux PPD; Mac OS X 10.8.5 to 10.11	Accessories (Order Numbers)	
Advanced networking & security	IPv6, 802.1x authentication, SNMPv3, SSL/TLS HTTPS encrpytion, Secure Print ² , Secure Erase ² , MAC filtering, IP filtering, IPSec	2nd paper tray	44274503
		3rd paper tray	44274503
Utility suite ¹	Template Manager ³ , Color Correct, OKI LPR ³ , Color Swatch Utility ³ , smart PrintSuperVision ³ , Print Job Accounting Client, Web Driver Installer ³ , Network Card Setup ⁵ , Configuration Tool ³ , PS Gamma Adjuster, PDF Direct Print ³ , Firmware Update Tool, Profile Assistant ⁶	Duplex	44274303 (Standard on ES7412dn)
		Memory	256MB: 44302203; 512MB: 44302207
		SDHC Memory Card4	16GB: 44301003
		Wireless LAN Module	45830202
		IC Reader Holder	46539501
TYPEFACES		Consumables (Order Num	
Printer fonts	Scalable: 87 PCL fonts and 80 PostScript fonts, PCL Bitmap fonts: LinePrinter, OCR-A/B, USPS ZIP Barcode	Toner cartridges*	Cyan: 46507639; Magenta: 46507638; Yellow: 46507637
Barcode	10 types of one dimension with 26 variations: UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved2of5, Code39, Code 128, EAN/UCC-128, CODABAR, ZIP+4POSTNET;2 types of two	(10,100 pages)	
		Toner cartridge* (10,700 pages)	
dimensions: PDF417, QR code PRINT QUALITY		Image drums** (30,000 pages)	
Resolution	ProQ2400 Multi-level technology, 1200 x 600dpi, 600 x 600dpi	Transfer Belt	
	Auto Colour Balance. Photo Enhance via driver	(60,000 pages)	45501102
Enhancements	(Windows PCL6 driver only)	ہ Fuser Unit (60,000 pages)	
PAPER HANDLING		*Toner: A4 pages @ 5% covera	
Paper capacity	Tray 1: 530 sheets of 80gsm; Multi-purpose tray: 100 sheets of 80gsm	Printer shipped with toner for 9,400 (CMY) and 9,900 (K) A4 pages @ 5% coverage. **Drum: Average number of A4 pages printed.	
Paper capacity optional trays	Tray 2: 530 sheets of 80gsm; Tray 3: 530 sheets of 80gsm		
Maximum paper capacity	1,690 sheets of 80gsm		
Paper sizes	Tray 1/2/3: A4, A5, B5; Multi-purpose tray: A4, A5, B5, A6; 10 Envelopes (Com-9, Com-10, DL, Monarch, C5); Labels (Avery 7162, 7664, 7666); Custom size (up to 1321mm length including Banner); Duplex : A4, A5, B5; Custom Size: Width 148- 215.9mm Length 210-355.6mm		
Paper weight	Tray 1/2/3: 64 to 220gsm; Multi-purpose tray: 64 to 250gsm; Duplex: 64 to 220gsm		
Duplex	Standard ES7412dn Optional ES7412n		

Paper output 350 sheets face down, 100 sheets face up (80gsm)

¹Check local OKI website for latest driver releases and OS compatibility; ²SDHC Memory Card required; ³Windows only; ⁴Secure Digital High Capacity (SDHC) Memory Card supports up to 32GB. OKI is not responsible for any compatibility risk using non OKI genuine SDHC Memory Card; ⁵Including all consumables; ⁶MacOSX only

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

Media Information: Certain types of media may not provide optimal results under default conditions.

*Available through the OKI Firmware Portal in 2017

OKI DATA AUSTRALIA PTY. LTD.

Level 1, 67 Epping Road Macquarie Park, NSW 2113 Australia T 1800 800 140 WWW.OKIEXECUTIVESERIES.COM.AU

OKI DATA NEW ZEALAND

8 Antares Place, Rosedale Auckland 0632 New Zealand T 0800 654 669 www.okiexecutiveseries.co.nz



3 Year On-site Warranty[^]

[^]Our devices are manufactured to the highest standards of quality and technology, which has been confirmed by independent tests. We are so convinced of the high quality of our products that we are offering you an extension of the standard warranty period to 3 years at no extra cost to you. Simply register your product within 30 days of purchase to be eligible for our unique all inclusive offer. Fully covered by OKI! For further information please visit: HTTP://WARRANTY.OKI.COM.AU (Australia) or HTTP://WARRANTY.OKI.COM.Z (New Zealand). Without registration, the standard 1 year warranty applies.





©2016 OKI Data Australia Pty. Ltd. OKI Data Australia Pty. Ltd. is part of the OKI Electric group of companies. Version 1.0 10/2016. Specification subject to change without notice. All trademarks acknowledged. Google Cloud Print is a trademark of Google Inc.