### **Pro9431dn Specifications**

## OKI



# A3 colour printer for professional quality output and unrivalled media flexibility

The Pro9431dn has been designed to meet the needs of the graphic arts and creative industries and is also well suited to general office applications, removing the need for two printers. Built to offer essential levels of high quality output, the Pro9431dn is robust and reliable, which are key requirements in these demanding markets.

The Pro9431dn is fully compatible with EFI Fiery XF 5.0 server which enables advanced colour management, including spot and process colours, optimising colour depth and print quality.

#### Stunning high definition colour

The Pro9431dn uses digital LED technology and our Multi-Level ProQ technology to produce high definition printing in the sharpest and most vibrant print output available.

- Superb print resolution of 1200 x 1200dpi
- Multi-Level ProQ technology enhances colour print output
- Fully compatible with EFI Fiery® XF for advanced colour management

#### Low total cost of ownership

The Pro9431dn delivers significant cost savings against comparative printers, combining a highly competitive capital cost with ultra-high capacity toner cartridges.

- Highly competitive initial capital cost
- Reduced operating costs through ultra-high capacity toner cartridges and drums
- Separate toners and drums for reduced wastage
- Energy efficient for reduced energy usage

#### Speed that you can rely upon

High print speeds with stunning high definition output that cannot be beaten.

- Time to first print less than 8 seconds
- A3 print speeds of 28ppm in colour/mono (up to 50ppm in colour/mono for A4)
- 2GB RAM and 1.2GHz processor for rapid throughput

#### Media flexibility to beat all others

The Pro9431dn beats the competition hands down when it comes to media flexibility, printing a complete range of media in-house.

- Widest paper handling A6 to SRA3 and banner lengths up to 1.3m
- Print on paper stock up to 360gsm single sided and 320gsm duplex
- Prints on a wide range of media including gloss paper, film, transfer paper, waterproof paper and more
- 530 sheet tray as standard, up to 2,950 sheets with optional trays
- Robust 300 sheet multi-purpose tray for added flexibility
- Duplex printing as standard



A3/A4	~
Colour/Mono	~
Prints A6 to 1321mm, up to 360gsm	~
1 - 30+ users	~

#### Pro9431dn - Colour and Mono Printer

PRINTER		OPERATOR PANEL		
Print speed	A4: 50ppm colour, 50ppm mono; A3: 28ppm colour, 28ppm mono	Display	10.9cm Colour Graphic LCD (480x272 dots)	
Time to first print	8 seconds colour, 8 seconds mono			
Warm up time	50 seconds or less from power on	<b>GENERAL FEATURES</b>		
Processor speed	1.2GHz	Memory	Standard RAM: 2GB; Maximum RAM: 2GB	
			Optional Hard Disk Drive: 160GB	
INTERFACE AND SOFTWARE			Operating temperature/humidity: 10°C to 32°C (17°C to 27°C	
Connectivity	Hi-Speed USB 2.0, 10Base-T/100Base-TX/1000Base-T	Environment	recommended) / 20% to 80% RH (50% to 70% RH recommended	
Printer languages	PCL5c, PCL6 (PCL XL), Adobe PostScript 3 with direct PDF	Power supply	Storage temperature/ humidity: -10°C to 43°C, 10% to 90% RI	
	All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IP: IPV4/v6, ICMP, ICMPv6, IGMP, IGMPv2, IPP. Dort0100 IPD IPDS FTP IFT Dover SCI. HTTP HTTPS TFINET	Power supply	Single phase 230V AC +/-10%, frequency 50/60Hz +/- 2%	
		Power consumption	Typical: 1100W; Max: 1600W; Idle: 40W (average); Power Save: <34W; Deep Sleep: <4W; Off Mode: <0.5W	
Network & protocols		Noise level	<b>Operating:</b> 57dB(A); <b>Standby:</b> 34dB(A) or less; <b>Power save:</b> Inaudible	
		Dimensions (HxWxD)	640 x 699 x 625mm	
		Weight <sup>4</sup>	97.6kg	
	Windows Vista (32-bit & 64-bit) / XP (32-bit & 64-bit) / Server 2003 (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Windows 7 (32-bit & 64-bit) / Server 2012 (64-bit) / Windows 8 (32-bit & 64-bit), Mac 059 / OS X 10.3.9	Duty cycle	Average: 25,000 pages/month; Maximum: 300,000 pages/month	
OS Compatibility <sup>1</sup>		Product order number	Pro9431dn: 45530407	
	- 10.9	Accessories (Order Numbers)		
	and security Sec, EAP-PEAP, EAP-TLS, Secure Erase <sup>3</sup> , Secure Print <sup>3</sup> , Secure Print Job Encryption <sup>3</sup> , Storage Devices entire Encryption <sup>3</sup> ,	2nd/3rd paper tray		
Advanced networking and security		2nd/3rd paper tray 2nd/3rd paper tray with castor	45530903	
		High Capacity Feeder	45530803	
	Adjuster, Profile Assistant (Mac Only), PDF Direct Print, EFI Fiery	Hard Disk Drive		
		EFI Fiery XF 5.0	Contact Oki for more information	
Utility suite <sup>1</sup>		Cabinet	45980001	
	XF Server Option (External color management server).	Consumables (Order Numbers)		
TYPEFACES		Toner cartridge* (42,000 pages)	Cyan: 45536555; Magenta: 45536554; Yellow: 45536553	
Printer fonts	87 scalable PCL fonts, Lineprinter/OCR-A/OCR-B/USPSZIP bit- map fonts, 10 TrueType fonts, 136 Adobe PostScript Type 1 fonts	Toner cartridge* (51,000 pages)	Black: 45536556	
Barcode	UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved 2of5, Code39, Code128, EAN/UCC-128, CODABAR, ZIP+4 POSTNET: PDF417/QR code 2D barcodes	Image drums** (40,000 pages)	Cyan: 45103721; Magenta: 45103720; Yellow: 45103719; Black: 45103722	
		Transfer Belt (150,000 pages)	45531213	
PRINT QUALITY		Fuser Unit	45531113	
Resolution	ProQ4800 Multi-level technology, 1200 x 1200dpi	(150,000 pages)		
Enhancements	Auto Colour Balance, Auto Registration, Auto Media Detect	Waste Toner Box (40,000 pages)	45531503	
PAPER HANDLING		*Toner: Number of A4 pages @ **Drum: Average number of A4	ISO coverage. Printer shipped with toner for 10,000 pages @ IS	
Paper capacity	Tray 1: 530 sheets of 80gsm; Multi-purpose tray: 300 sheets of 80gsm	Drum: Average number of A4	pages printeu.	
Paper capacity optional trays	Tray 2: 530 sheets of 80gsm; Tray 3: 530 sheets of 80gsm; High Capacity Feeder: 1,590 sheets of 80gsm			
Maximum paper capacity	2,950 sheets of 80gsm			
Paper sizes	Tray 1/2/3: A3, SRA3 (up to 330 x 457mm), SRA4, A4, A5, A6, B4, B5, B6; Multi-purpose tray: A3, SRA3, SRA4, A4, A5, A6, B4, B5, B6 Custom size: Width 64 - 330mm Length 89 - 1,321mm; High Capacity Feeder: A3, SRA3 (up to 328 x 672mm) SBA4, A4, BF, A6, BA, BF, BF, BC			

Paper output 610 sheets face down tray, 300 sheets face up tray

Paper weight

Duplex Standard

457mm), SRA4, A4, A5, A6, B4, B5, B6

<sup>1</sup>Check local OKI website for latest driver releases and OS compatibility; <sup>2</sup>Windows only; <sup>3</sup>HDD required; <sup>4</sup>Including all consumables

Tray 1/2/3: 52 to 320gsm; Multi-purpose tray: 52 to 360gsm; Duplex: 64 to 320gsm; High Capacity Feeder: 52 to 320gsm

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

#### OKI Systems (UK) Ltd.

Blays House, Wick Road Egham, TW20 0HJ United Kingdom +44(0) 1784 274300 WWW.OKI.CO.UK

